



<b>BN 21412</b>
<b>Blind rivets Standard</b>
dome head
Copper
polished
<ul style="list-style-type: none"> <li>Rivet: copper</li> <li>Mandrel: steel zinc plated</li> </ul>

**i** The specified shear and tensile forces are minimal values.

Article#	d1	±	d2	±	d3~	s	±	L1 min.				L (+1/-0,2)		Code
3684784	3	+0,08/-0,1	6,5	+0/-0,7	1,8	0,9	0,2	27	3,1	800	700	6	1-3	FSD-3006CUST
3684783												8	3-5	FSD-3008CUST
3684782												10	5-7	FSD-3010CUST
3684781												12	7-9	FSD-3012CUST
3684780	3,2	+0,08/-0,1	6,5	+0/-0,7	1,8	0,9	0,2	27	3,3	900	800	6	1-3	FSD-3206CUST
3684779												8	3-5	FSD-3208CUST
3684778												10	5-7	FSD-3210CUST
3684777												12	7-9	FSD-3212CUST
3684776	4	+0,08/-0,15	8	+0/-1	2,2	1	0,3	27	4,1	1500	1000	6	1-2,5	FSD-4006CUST
3684775												8	2,5-4,5	FSD-4008CUST
3684774												10	4,5-6,5	FSD-4010CUST
3684773												12	6,5-8,5	FSD-4012CUST
3684772												14	8,5-10	FSD-4014CUST
3684771												16	10-12,5	FSD-4016CUST
3684770	4,8	+0,08/-0,15	9,5	+0/-1	2,78	1,1	0,3	27	4,9	2000	1500	8	2,5-4	FSD-4808CUST
3684769												10	4-6	FSD-4810CUST
3684768												12	6-8	FSD-4812CUST
3684767												14	8-10	FSD-4814CUST
3684766												16	10-12	FSD-4816CUST
3684765												18	12-14	FSD-4818CUST
3684764												20	14-16	FSD-4820CUST