



BN 21404

Blind rivets Standard

countersunk head

Steel

zinc plated

- Rivet / Mandrel: steel



The specified shear and tensile forces are minimal values.

Article#	d1	±	d2	±	d3~	s~	L1 min.				L (+1/-0,2)		Code
3684483	3	+0,08/-0,1	6	+0/-0,4	1,92	0,9	27	3,1	1100	850	6	1,5-3,5	FSC-3006STST
3684482											8	3-5	FSC-3008STST
3684481											10	5-6,5	FSC-3010STST
3684480											12	6,5-8	FSC-3012STST
3684479											14	8-10	FSC-3014STST
3684478	3,2	+0,08/-0,1	6	+0/-0,4	1,92	0,9	27	3,3	1380	1160	6	1,5-3	FSC-3206STST
3684477											8	3-5	FSC-3208STST
3684476											10	5-6,5	FSC-3210STST
3684475											12	6,5-8	FSC-3212STST
3684474											14	8-10	FSC-3214STST
3684473											16	10-12	FSC-3216STST
3684472	4	+0,08/-0,15	7,5	+0/-0,5	2,42	1	27	4,1	2200	1700	6	2-3	FSC-4006STST
3684471											8	3-5	FSC-4008STST
3684470											10	5-6,5	FSC-4010STST
3684469											12	6,5-8	FSC-4012STST
3684468											14	8-10	FSC-4014STST
3684467											16	10-12	FSC-4016STST
3684466											18	12-14	FSC-4018STST
3684465											20	14-16	FSC-4020STST
3684464	4,8	+0,08/-0,15	9	+0/-0,5	2,92	1,2	27	4,9	3100	2400	8	2,5-4	FSC-4808STST
3684463											10	4-6	FSC-4810STST
3684462											12	6-8	FSC-4812STST
3684461											14	8-9,5	FSC-4814STST
3684460											16	9,5-11	FSC-4816STST
3684459											18	11-13	FSC-4818STST
3684458											20	13-15	FSC-4820STST
3684457											25	15-19,5	FSC-4825STST

Article#	d1	±	d2	±	d3~	s~	L1 min.				L (+1/-0,2)		Code
3684456	5	+0,08/-0,15	9	+0/-0,5	2,92	1,2	27	5,1	4000	2600	8	2,5-4	FSC-5008STST
3684455											10	4-6	FSC-5010STST
3684454											12	6-8	FSC-5012STST
3684453											14	8-9,5	FSC-5014STST
3684452											16	9,5-11	FSC-5016STST
3684451											18	11-13	FSC-5018STST
3684450											20	13-15	FSC-5020STST
3684449											25	15-19,5	FSC-5025STST