



BN 30102
Hex socket button head cap screws
partially / fully threaded
Steel 010.9
zinc plated blue

! ISO 4042
 Fasteners hardness ≥ 320 HV with electroplated coatings:
 Susceptible to hydrogen embrittlement!
 Further notice to residual risks can be found in the introduction section.

i Fasteners to the given specification have a reduced loadability due to the head geometry according to ISO 898-1.

b: the partially threaded version can not always be guaranteed

Article#	d ₁	d ₂ max.	k max.	s	t min.	b	L
3167668	M4	7,6	2,2	2,5	1,3	-	6
3167669							8
3167670							10
3167671							12
3167672							16
8256993							20
8277478							25
8277486						20	30
5400638	M5	9,5	2,75	3	1,56	-	8
5400639							10
5400640							12
5400641							16
5400642							20
5400643							25
5400644						22	30
5400645							35
5400646							40
3299351							50
5400647	M6	10,5	3,3	4	2,08	-	8
5400648							10
5400649							12
5400650							16

b: the partially threaded version can not always be guaranteed

Article#	d ₁	d ₂ max.	k max.	s	t min.	b	L
5400651	M6	10,5	3,3	4	2,08	-	20
5400652							25
5400653							30
5400654						24	35
5400655							40
5116021							45
3170925							50
5400656	M8	14	4,4	5	2,6	-	10
5400657							12
5400658							16
5400659							20
5400660							25
5400661							30
5400662							35
5400663						28	40
8277621							45
5400664							50
8277672							55
8277699							70
5400665	M10	17,5	5,5	6	3,12	-	16
5400666							20
5400667							25
5400668							30
5400669							35
5400670							40
5400671						32	50
8277710							60
5111615	M12	21	6,6	8	4,16	-	45
5111623						36	55